

# Industrial Temperature Sensor

Featuring LoRaWAN®

## NI500PT100



NI500PT100 resistance temperature sensor is designed for measuring wide range of temperature in harsh environments and transmitting data using LoRaWAN® technology. With this low power consumption technology, NI500PT100 can work up to 10 years with 19000 mAh battery. Combining with LoRaWAN® gateway and IoT Cloud solution, users can manage all sensor data remotely and visually.

EM500-PT100 is widely used for temperature monitoring applications like industrial machines, ovens, pipes, etc.

### ◆ Features

- Corrosion resistance cable and multiple probe options
- 3 wire connection for high precision
- Ultra-wide-distance transmission up to line of sight of 10km
- IP67 waterproof enclosure for harsh environment applications
- Built-in 19000 mAh replaceable battery and work for 10 years without replacement
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with IoT Cloud solution

### ◆ Applications

- Liquid or gas monitoring
- Industrial machine monitoring
- Oven and cooking monitoring
- Chimney and boiler temperature monitoring
- Medical or laboratory use

## ◆ Specifications

<b>Wireless Transmission</b>	
Technology	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-137dBm @300bps
Mode	OTAA/ABP Class A
<b>Measurement</b>	
Connection Type	3-wire connection
Range	T050: -200 °C to +50 °C T200: -50 °C to +200 °C T500: -50 °C to +500 °C T800: -50 °C to +800 °C (Customizable from -200 °C to +800 °C)
Accuracy	±0.5°C
Resolution	0.1°C
<b>Operation</b>	
Power On & Off	Power button (Internal)
Configuration	PC software(via USB Type-C)
<b>Physical Characteristics</b>	
Cable Length	1.5 m (Customizable)
Probe Type	Straight tube (Customizable)
Power Supply	19000 mAh Li-SOCL <sub>2</sub> battery (ER34615)
Battery Life*	10 years (10 min interval)
Operating Temperature	-30°C to +70°C
Relative Humidity	0% to 100% (non-condensing)
Ingress Protection	Transceiver: IP67, Sensor: differ based on temperature ranges
Dimension	105.4 × 71 × 69.5 mm (4.1 × 2.8 × 2.7 in)
Installation	Pole, wall or DIN Rail Mounting
<b>Approvals</b>	
Regulatory	CE, FCC, RoHS

\* Tested under laboratory conditions and for guideline purposes only.